

CaF₂ 99.8% 0.7-3.5mm 500g - 0481329

Specifications

| | |
|--|------------------|
| Coating material | Calcium fluoride |
| Purity | 99.8% |
| Form | Granulate |
| Dimensions | 0.7 - 3.5 mm |
| Quantity | 500 g |
| Theoretical density at 20°C in g/cm ³ | 3.2 |
| Melting point in °C | 1423 |

Temperature at vapor pressure

| | |
|-----------------------------|--------|
| 10 ⁻² mbar in °C | 1280 |
| 10 ⁻¹ mbar in °C | 1410 |
| Boiling point in °C | ~ 2500 |

Type of evaporation

| | |
|---------|----------|
| Melting | Possible |
|---------|----------|

Evaporation source (typically)

E-gun

Liner material

| | |
|----|------|
| Mo | Good |
|----|------|

Boat

Boat material

| | |
|----|------|
| W | Good |
| Ta | Good |

Specific evaporation conditions

| | |
|------------------------------------|------|
| Preparation of base melt (premelt) | Good |
| Low residual pressure | Good |

Substrate temperature range

| | |
|--------------|------|
| 100 - 200 °C | Good |
| 200 - 300 °C | Good |

Film transparency

| | |
|------|------|
| Low | 0.15 |
| High | 12 |

Film refractive index n / extinction coefficient k

| | |
|--------------|-----------|
| at 550 nm: n | 1.23-1.46 |
|--------------|-----------|